



# 富高

## FUKKOL

### Product Bulletin

一切決擇於潤滑  
DECISION EVERYTHING OF LUBRICANT

安全第一

## 富高齒富齒輪油系列 FUKKOL GEARFUL GEAR OIL



### Description

Industrial gear lubricants intended for enclosed gear sets operating under severe service conditions. They provide outstanding anti-wear and friction reducing characteristics, enhanced oxidation stability, protection from corrosion and resistance from foaming as the result of a unique additive system.

### Application

For all types of enclosed gear drives with circulation or splash lubrication systems. Particularly recommended for gear sets working under heavy or shock conditions up to operating temperatures of 110°C. (For wormgears the build oil temperature is usually restricted to 95°C.)

### 簡介

齒富系列是一組工業用齒輪潤滑油，專用於嚴厲工作環境下操作之密閉式齒輪組。因為採用特殊的添加劑配方，本組齒輪油有突出的抗磨損及減低磨擦力的性能，抗氧化穩定性特強，並且有防腐蝕及抗泡沫的特性。

### 用途

適合各種採用循環式或飛濺式潤滑方法的密閉式齒輪。特另適合用於負荷重或受衝擊性負荷而油溫在攝氏95度以下。（用於蝸齒輪時，油溫通常限于攝氏95度以下）

### Characteristics 特性

ISO viscosity grade ISO 黏度等級	68	100	150	220	320	460	680
Specific gravity 比重	0.890	0.892	0.895	0.900	0.905	0.915	0.92
Pour point, 傾点	-24	-23	-24	-18	-18	-6	-6
Flash point, °C 閃火点, °C	204	207	210	216	232	232	232
Viscosity cst at 40°C 黏度 40°C 厘沲	64.5	95	142.5	209	304	437	646
Cst at 100°C 100°C 厘沲	8.2	11.8	15.0	17.8	22.5	30.4	33.6
Ciscosity index 黏度指數	95	95	95	95	95	95	90